

MAINTENANCE-FREE MOTORCYCLE BATTERY


EBX7L-BS (12V6Ah)














GENERAL FEATURES

- · Sealed AGM battery
- · Rest after filling acid
- Fresh Pack, Maintenance-Free

*Values are subject to variation of +/- 5% in normal manufacturing processes.


Leoch International Technology Ltd. www.leoch.com

Leoch Batteries Pte Ltd www.leoch.sg

CHARACTERISTICS

Item		Specifications
Nominal Voltage		12V
Nominal Capacity (10HR)		6Ah
Cold Cranking Performance Amps@0°F (-18°C)		C) 85A
Dimension (±2mm)	Length	113mm (4.45inches)
	Width	70mm (2.76inches)
	Container Height	130mm (5.12inches)
	Total Height	130mm (5.12inches)
Battery (with acid)	Approx Weight	2.36kg (5.20lbs)
Electrolyte	Approx Weight	0.44kg (0.970lbs)
Terminal type		A
Battery type	Dry Charged Series	
Full Charge	Constant-Voltage Charg	ge:
	Initial charging current	Less than 0.3C10
	Voltage	14.40V~15.00V at 25°C (77°F)
	Charging time	15~18h
	Constant-Current Charge	ge:
	Charging current 0.1C10 14.40V, continue to cha	o, when charging voltage up to arge 4h
Floating Charge	Initial charging current	Unlimited
	Voltage	13.50V~13.80V at 25°C (77°F)
Capacity affected by Temperature	40°C (104°F)	106%
	25°C (77°F)	100%
	0°C (32°F)	86%
	-15°C (5°F)	65%

Discharge Characteristics (25°C, 77°F)



Leoch Battery Corporation www.leoch.us

Leoch Europe S.A. www.leoch.eu

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.

Publication No.:LB-EBX7L-BS-PD-EN-V1.0-20230815